



Hy-Lok Tube Fittings

Female Adapter CAF



1 in. / 25mm and under.



Over 1 in. / 25mm

Connects Fractional Hy-Lok Port to Male NPT Thread

Part No.	Tube O.D. D		T* NPT Size	d Min.	Width across flat h (in.)	L
	in	mm				
CAF 2 - 2N	1/8	3.17	1/8	2.03	9/16	31.50
CAF 2 - 4N	1/8	3.17	1/4	2.03	3/4	35.30
CAF 3 - 2N	3/16	4.76	1/8	3.04	9/16	32.00
CAF 3 - 4N	3/16	4.76	1/4	3.04	3/4	35.81
CAF 4 - 2N	1/4	6.35	1/8	4.32	9/16	33.02
CAF 4 - 4N	1/4	6.35	1/4	4.32	3/4	37.10
CAF 4 - 6N	1/4	6.35	3/8	4.32	7/8	39.37
CAF 4 - 8N	1/4	6.35	1/2	4.32	1-1/16	45.50
CAF 5 - 2N	5/16	7.93	1/8	5.59	9/16	34.29
CAF 5 - 4N	5/16	7.93	1/4	5.59	3/4	37.59
CAF 6 - 2N	3/8	9.52	1/8	6.86	9/16	34.29
CAF 6 - 4N	3/8	9.52	1/4	6.86	3/4	38.10
CAF 6 - 6N	3/8	9.52	3/8	6.86	7/8	40.38
CAF 6 - 8N	3/8	9.52	1/2	6.86	1-1/16	46.73
CAF 8 - 4N	1/2	12.70	1/4	9.40	3/4	43.43
CAF 8 - 6N	1/2	12.70	3/8	9.40	7/8	45.46
CAF 8 - 8N	1/2	12.70	1/2	9.40	1-1/16	51.80
CAF10 - 6N	5/8	15.87	3/8	11.94	7/8	48.26
CAF10 - 8N	5/8	15.87	1/2	11.94	1-1/16	53.00
CAF10 - 12N	5/8	15.87	3/4	11.94	1-5/16	55.37
CAF12 - 8N	3/4	19.05	1/2	14.73	1-1/16	52.83
CAF12 - 12N	3/4	19.05	3/4	14.73	1-5/16	54.86
CAF12 - 16N	3/4	19.05	1	14.73	1-5/8	58.42
CAF14 - 12N	7/8	22.22	3/4	18.20	1-5/16	57.15
CAF16 - 12N	1	25.40	3/4	20.32	1-5/16	60.70
CAF16 - 16N	1	25.40	1	20.32	1-5/8	64.26
CAF20 - 20N ^①	1-1/4	31.75	1-1/4	25.91	2-1/8	77.72
CAF24 - 24N ^①	1-1/2	38.10	1-1/2	31.75	2-3/8	88.90
CAF32 - 32N ^①	2	50.80	2	43.69	2-7/8	107.44

* ISO Tapered Threads are available upon request.

① Furnished with nut and preswaged ferrules.

Connects Metric Hy-Lok Port to Male ISO Tapered Thread

Part No.	Tube O.D. D	T* NPT Size	d Min.	Width across flat h	L
CAF 3M - 2R	3	1/8	1.9	14	31.15
CAF 6M - 2R	6	1/8	4.1	14	32.50
CAF 6M - 4R	6	1/4	4.1	19	37.10
CAF 8M - 4R	8	1/4	5.6	19	37.60
CAF10M - 4R	10	1/4	7.1	19	38.10
CAF10M - 6R	10	3/8	7.1	22	40.10
CAF10M - 8R	10	1/2	7.1	27	46.50
CAF12M - 4R	12	1/4	8.8	19	43.70
CAF12M - 6R	12	3/8	8.8	22	46.00
CAF12M - 8R	12	1/2	8.8	27	52.30
CAF18M - 12R	18	3/4	13.9	35	54.80

* NPT Threads are available upon request.